

Product Specifications

Style Name	Contrax II HD Modular
Style Number	10026
Surface Texture	Level Loop
Pile Fibre Content	100% BFC Colorloc nylon
Dye System	Solution Dyed
Primary Backing	Non-Woven Polyester
Secondary Backing	Fiberglass Reinforced Thermoplastic - PermaFuse Technology - Phthalate Free


	<u>Imperial</u>	<u>Metric</u>
Pile Weight	24.0 oz / s.y.	814 g/m2
Gauge	1/10 ga	39.4 / 10 cm
Stitches	8.0 / in.	31.5 / 10 cm
Pile Height	0.236 in.	6.0 mm
Pile Thickness	0.118 in.	3.0 mm
Density Factor	7322	10.92 ktex
Total Weight	115.05 oz / s.y.	3900 g/m2

Performance Specifications


Flammability	Meets ASTM E-648 test standards Radiant Panel Class I
Smoke Density	Meets ASTM E-662 test standards <450 Flaming mode
Anti-Static Properties	Less than 3.0 kv at 20% R.H.. & 21° C
Dimensional Stability	Less than 0.05 %
Lightfastness	L5 or Better
Resistance to Wet Cleaning	Grey Scale 5
Acoustique ASTM-E3133	70
Acoustique ASTM-E492	60
Installation Method	



Quarter-Turn



Brick



Ashlar

Warranty Information

- Lifetime Limited Commercial Wear & Anti-Static
- Lifetime Limited Commercial Against Delamination
- Lifetime Limited Commercial on Dimensional Stability
- Lifetime Limited Against Backing Deterioration

Environmental

Indoor air quality no.	GLP 3315
------------------------	----------

Dimension

Carpet Tile (PermaFuse)	19.68" x 19.68"	50 cm x 50 cm
Broadloom (PermaFuse XL)	79.25"	201 cm
UNILOC Commercial Unitary Backing System	79.25"	201 cm
Pattern Repeat for Roll	81" x 81"	205.74 cm x 205.74 cm

Manufacturer reserves the right to modify the specification to improve this product without prior notice and without prejudice