

Modular

Product Specifications


Style Name	Nanaimo
Style Number	40207
Surface Texture	Multilevel Loop
Pile Fibre Content	100% Aquafil BCF Anti-Static ECONYL nylon
Dye System	Solution Dyed
Primary Backing	Non-Woven Polyester
Secondary Backing	Fiberglass Reinforced Thermoplastic - PermaFuse Technology - Phthalate Free

	<u>Imperial</u>	<u>Metric</u>
Pile Weight	17.0 oz / s.y.	576 g/m2
Gauge	1/12 ga	47.2 / 10 cm
Stitches	12.5 / in.	49.2 / 10 cm
Pile Height	0.177 in.	4.5 mm
Pile Thickness	0.118 in.	3.0 mm
Density Factor	5186	9.57 ktex
Total Weight	108.03 oz / s.y.	3662 g/m2

Performance Specifications

Flammability	Meets ASTM E-648 test standards Radiant Panel Class I
Smoke Density	Meets ASTM E-662 test standards <450 Flaming mode
Anti-Static Properties	Less than 3.0 kv at 20% R.H.. & 21° C
Dimensional Stability	Less than 0.05 %
Lightfastness	L5 or Better
Resistance to Wet Cleaning	Grey Scale 5
Acoustique ASTM-E3133	70
Acoustique ASTM-E492	60

Installation Method's



Classic

Herringbone

Warranty Information

- Lifetime Limited Commercial Wear & Anti-Static
- Lifetime Limited Commercial Against Delamination
- Lifetime Limited Commercial on Dimensional Stability
- Lifetime Limited Against Backing Deterioration

Environmental

Indoo air quality no. GLP 3315

Dimension

Tile (PermaFuse)	9.84" x 39.37"	25 cm x 100 cm
------------------	----------------	----------------

Manufacturer reserves the right to modify the specification to improve this product without prior notice and without prejudice