



Modular

Product Specifications

Style Name	Tofino
Style Number	40199
Surface Texture	Multilevel Loop
Pile Fibre Content	100% BCF Olefin-Velana
Dye System	Solution Dyed
Primary Backing	Non-Woven Polyester
Secondary Backing	Fiberglass Reinforced Thermoplastic - PermaFuse Technology - Phthalate Free

	<u>Imperial</u>	<u>Metric</u>
Pile Weight	18.0 oz / s.y.	610 g/m2
Gauge	1/12 ga	47.2 / 10 cm
Stitches	11.0 / in.	43.3 / 10 cm
Pile Height	0.138 in.	3.5 mm
Pile Thickness	0.098 in.	2.5 mm
Density Factor	6612	12.26 ktex
Total Weight	109.03 oz / s.y.	3696 g/m2


Performance Specifications

Flammability	Meets ASTM E-648 test standards Radiant Panel Class II
Smoke Density	Meets ASTM E-662 test standards <450 Flaming mode
Anti-Static Properties	Less than 3.0 kv at 20% R.H.. & 21° C
Dimensional Stability	Less than 0.05 %
Lightfastness	L5 or Better
Resistance to Wet Cleaning	Grey Scale 5
Acoustique ASTM-E3133	70
Acoustique ASTM-E492	60


Installation Method's



Quarter-Turn



Brick



Ashlar

Warranty Information

- 10 years Limited Commercial Wear & Anti-Static / 20 years Limited Residential Wear & Anti-Static
- 10 years Limited Commercial Against Delamination / 20 years Limited Residential Against Delamination
- 10 years Limited Commercial on Dimensional Stability / 20 years Limited Residential on Dimensional Stability
- 10 years Limited Commercial Against Backing Deterioration / 20 years Limited Residential Against Backing Deterioration

Environmental

Indoo air quality no.	GLP 0006
-----------------------	----------

Dimension

Tile (PermaFuse)	19.68" x 19.68"	50 cm x 50 cm
------------------	-----------------	---------------

Manufacturer reserves the right to modify the specification to improve this product without prior notice and without prejudice